

**To: All Competitors**  
**From: The Rock – Allegany Co. Speedway Technical Inspection Staff**  
**Re: 2009 Season Rule Changes**

## 2009 Season Summary of Technical Rule Changes

*Listed by corresponding section to the rule guidelines per class. Changes to existing language is underlined in red.*

### Limited Late Model

Section 23A: Minimum Weight

- 2400 lbs. for 358 c.i. engine limit

- 2550 lbs. for over 358 c.i. engine

### Street Stock

Section 3A. Bodies must be steel bodies of original factory design.

Section 10E. Clutch must be stock or triple disk only; no smaller than 7.25 inches in diameter.

Section 12A. Engine size not to exceed 412 CID

Section 13A. (Removed reference to Dorton 80583).

Section 14A. All cars up to 358 CID must weight a minimum of 3000 lbs. and all cars over 358 CID must weigh 3300 lbs. after race with driver.

Section 15B. Five (5) point racing harness (seat belts) less than three years old required.

### Hobby Stock

Section 8M. Stock two barrel Rochester carburetors with no modifications. One and three-eighth (1 3/8) Venturi size will be checked ...

Section 12B. Hoosier 500 size 8.0-27.0-15 or American Racer dirt size 70/245 15 hard compound only. E-mod tires hard compound only.

Factory Stock 4-Cylinder

No changes.

Factory Stock 6-Cylinder

No changes.

Factory Stock 8-Cylinder

No changes.